


ROME

Series:

AH

Hinge Wheel Offset Disk Harrow

For use with tractors in the 217 – 384hp range.



FEATURES:

- The patented Hinge Wheel Offset Disk Harrow line was designed by ROME engineers to meet today's high residue needs. Ruggedly built it is ideally suited for plowing, light plowing, pulverizing, and plowing stubble.
- The unique concept combines the superior uniform leveling and mixing capability of a hinge harrow with the convenient transportability of a wheel harrow.
- Gang assembly design positions the bearing and spacer assemblies behind the gang carriers providing additional clearance resulting in excellent trash handling capabilities.
- Full range of adjustments allows the precise control of penetration depth hydraulically.
- "On the go" angle adjustments from 0° to 45° are hydraulically controlled from the operator's seat.
- Equipped with Timken dual tapered roller bearings with cast housings.
- Standard heavy duty bearing wear plates help protect the bearing housing from wear caused by abrasive soils, extending their service life and reducing cost.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series AH Hinge Wheel Offset Disk Harrow

14" (356mm) disk spacing; 2-1/8" (54mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Number of Tires	Net Weight lbs (kg)
AH-200	10'-6" (3.2)	20	217 – 253	448 (203)	2	8698 (3945)
AH-240	13'-0" (4.0)	24	253 – 286	429 (195)	4	10,299 (4672)
AH-280	15'-0" (4.6)	28	298 – 334	431 (196)	4	12,070 (5475)
AH-320	17'-6" (5.3)	32	333 – 366	416 (189)	4	13,320 (6042)
AH-360	20'-0" (6.1)	36	349 – 384	389 (177)	4	14,001 (6351)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuits required for harrow operation.

Standard Equipment:

- 32" (813mm) diameter x 3/8" (10mm) thick, cutout (notched) deep concavity disk blades.
- Adjustable disk blade scrapers.
- Heavy duty bearing wear plates.
- New industrial tires. AH-200 – 12.5L x 16 – 12 ply. AH-240 thru AH-360 – 12.5L x 16 – 12 ply.
- Drawbar jack stand and safety chain.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.

Optional Equipment:

- Rear hitch assembly.
- Rear hydraulic group.
- Furrow filler group.
- Extra heavy duty wear plates.
- 32" (813mm) diameter x 3/8" (10mm) thick dura-faced cutout (notched) deep concavity disk blades.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com