



Series:

240

Double Offset Tandem Disk Harrow

For use with tractors in the 275 – 500hp range.



FEATURES:

- Four gauge wheel assemblies provide a consistent depth of penetration on all four gangs while providing accurate leveling.
- Double offset tandem disk harrow series is ideally suited to provide excellent uniform tillage results in all plowing applications
- Main frame and gang carriers constructed of tough high strength tubular steel, welded for maximum strength and durability.
- Transport position allows for approximately 10" (254mm) of ground clearance with standard 24" (610mm) diameter disk blades.
- Equipped with reliable, heavy duty, dual tapered 9" (229mm) self-aligning oil-bath gang roller bearings with cast housings.
- Bearing wear plates help protect the bearing housing from wear caused by abrasive soils extending their service life and decreasing cost.
- Up to 8" (204mm) depth of penetration.
- Tapered gang assemblies mounted on rock flex standards.



Scan the code to visit our website today:
www.romeplow.com



Specifications:

Series 240 Double Offset Tandem Disk Harrow

9" (229mm) disk spacing; 1-5/8" (41mm) round axles; Equipped with self-aligning oil bath dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Transport Height ft/in (m)	Transport Width ft/in (m)	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Number of Bearings	Net Weight lbs (kg)
240-984	32'-0" (9.8)	84	13'-1" (4.0)	16'-4" (5.0)	275 – 450	262 (119)	24	22,000 (9979)
240-994	36'-0" (11)	94	15'-9" (4.8)	16'-4" (5.0)	325 – 500	250 (114)	24	23,500 (10,659)

* Engine horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. Two rear tractor hydraulic circuits required for harrow operation.

Standard Equipment:

- 24" (610mm) diameter x 1/4" (6mm) thick, smooth (round) shallow concavity disk blades.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacers.
- Eight 12.5L x 15 – F1 highway service tires for easy plowing, turning, and transporting.
- Heavy duty 8 bolt wheel hubs with 2 tapered roller bearings on each hub with moisture protection.
- Tandem walking beam transport.
- Four gauge wheel groups.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Hardened pins and bushings on all pivot points.

- Adjustable disk blade scrapers.
- Rock flex standards.
- Drawbar jack stand.

Optional Equipment:

- 24" (610mm) diameter x 1/4" (6mm) thick, cutout (notched) front and smooth (round) rear shallow concavity disk blades.
- 24" (610mm) diameter x 1/4" (6mm) thick, cutout (notched) front and rear shallow concavity disk blades.
- Rear hitch assembly.
- Rear hydraulic group.
- Heavy duty bearing wear plates with 1/4" (6mm) hard plate overlay.
- Light group.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com