



Series:

TCW

Wheel Offset Disk Harrow

For use with tractors in the 30 – 114hp range.



FEATURES:

- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- High gang carrier design to prevent trash build up and clogging.
- Levels, cuts, and mixes to full working depth.
- Combines ease of maneuverability with high strength for the most adverse conditions.
- Up to 178lbs (81kg) of weight per disk blade depending on model with an average of 171lbs (78kg).
- Up to 8" (203mm) maximum depth of penetration with standard 24" (610mm) diameter disk blades.
- Equipped with Timken dual tapered roller bearings.
- Adjustable disk blade scrapers.
- Dual purpose transport unit for transportability and penetration control.



Scan the code to visit our website today:
www.romeplow.com



Specifications:

Series TCW Wheel Offset Disk Harrow

9-1/2" (241mm) disk spacing; 1-5/8" (41mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TCW-16	6'-0" (1.8)	16	30 – 56	175 (79)	2813 (1276)
TCW-18	7'-0" (2.1)	18	32 – 57	171 (78)	3082 (1398)
TCW-20	7'-6" (2.3)	20	38 – 65	177 (80)	3557 (1613)
TCW-24	9'-0" (2.7)	24	48 – 73	165 (75)	3982 (1806)
TCW-28	10'-6" (3.2)	28	54 – 87	178 (81)	4984 (2261)
TCW-32	12'-0" (3.7)	32	73 – 98	174 (79)	5576 (2529)
TCW-36	14'-0" (4.3)	36	77 – 102	164 (74)	5923 (2687)
TCW-40	15'-6" (4.7)	40	89 – 114	166 (75)	6660 (3021)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 24" (610mm) diameter x 1/4" (6mm) thick, cutout (notched) deep concavity disk blades.
- Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. TCW-16 thru TCW-24: 12.5L x 15 – 12 ply. TCW-28 and TCW-32: 7.5 x 16 – 12 ply. TCW-36 and TCW-40: 12.5L x 15 – 12 ply.

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Two heavy duty gang wrenches.
- Drawbar jack stand and safety chain.

Optional Equipment:

- 26" (660mm) diameter x 1/4" (6mm) thick, cutout (notched) deep concavity disk blades.
- Cylinder rod stops for positive depth control adjustment.
- Drawbar clevis for track type tractors



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com